Innovation for Our Energy Future

GIS Data Manipulation and Economic Modeling Issues and Examples

Geospatial Statistics and Issues in Energy Modeling Workshop

May 10, 2005

Ray George, Donna Heimiller, Anelia Milbrandt, Liz Brady Sabeff



Overview

- GIS Generated Resource Supply Curves
- Uncertainty In Estimating Biomass Spatial Distribution
- Uncertainty In Solar Radiation Estimates
 Based On Input Data
- Potential Data Sets For Regionalization
 To Support National Level Models



GIS Generated Resource Supply Curves

- GIS analysis can be used to generate supply curves for regional models
 - Take advantage of higher resolution datasets
 - Account for cost factors with spatial components
 - Transmission line length
 - Slope
- Limited to setting up initial conditions




WinDS – Regional Supply Curves

- Original wind resource resolution varies from 200 m to 25 km
 - Resource is resampled to 200 m cell size and separated by power class
 - Resource aggregated to 3 km cells
 - Aggregation needed for processing
 - Preserve wind class distribution
 - Cells much smaller than WinDS regions

Wind to Transmission Line Assignment

- Assign lowest cost wind cells first
- Cost based on:
 - Wind power class
 - Distance to transmission line/load
 - Slope (starting region)
 - Population density (starting region)
- Continues until all wind is assigned or all transmission capacity is used




Generate Regional Supply Curves

| Region | WPC | Costbin | |
|--------|-----|---------|---------|
| 1 | 7 | 34 | 51.3200 |
| 1 | 7 | 35 | 37.9600 |
| 1 | 7 | 36 | 7.2400 |
| 1 | 7 | 37 | 5.4800 |
| 1 | 7 | 38 | 2.6000 |
| 1 | 7 | 39 | 0.2800 |
| 1 | 7 | 41 | 0.8400 |
| 1 | 7 | 44 | 0.2000 |
| 1 | 7 | 45 | 0.6200 |
| 1 | 6 | 35 | 15.8000 |
| 1 | 6 | 36 | 19.4400 |
| 1 | 6 | 37 | 10.9200 |
| 1 | 6 | 38 | 6.9800 |
| 1 | 6 | 39 | 9.8600 |
| 1 | 6 | 40 | 3.2000 |
| 1 | 6 | 41 | 21.9800 |
| 1 | 6 | 42 | 30.8400 |
| 1 | 6 | 43 | 9.2800 |
| 1 | 6 | 44 | 5.2400 |
| 1 | 6 | 46 | 8.0000 |
| 1 | 6 | 48 | 0.4600 |
| 1 | 6 | 49 | 6.0200 |
| 1 | 6 | 50 | 18.4800 |
| 1 | 6 | 51 | 3.0000 |
| 1 | 6 | 53 | 1.8600 |
| 1 | 5 | 42 | 10.0800 |
| | | | 10.000 |

- GIS system tracks for each resource points:
 - Cost assigned at
 - Amount of area assigned
 - Region the resource is in
 - Transmission line assigned to
- Build supply curves by summarizing resource by power class and cost bin for each source region

WinDS – Regional Supply Curves



- Cost factors don't have to be linear
- Assigned cost can be aggregated to other regions (states)
- Can only reflect initial conditions

How can spatial statistics help?

- What is appropriate starting aggregation size for resource?
 - 3 km picked through trial and error
 - Technology specific factors?
- Load allocation
- Information on spatial correlation of resource
- Predict/extrapolate regional demand growth rates






Uncertainty in Estimating Biomass Spatial Distribution

- Residue data reported by county
- Possible data to support better spatial distribution
 - Land use (crop and forest residues) 1km or better
 - Animal farm locations (animal manure)
 - Mill locations
 - Landfill locations

NREL's biomass assessment is based on statistical data that is reported by county to USDA, Forest Service, EPA

Differences in Spatial Distribution




Importance of spatial distribution of Biomass

- Transportation and transmission proximity for cost analyses
- Building more precise supply curves
- Co-firing with conventional fuels
- Power plant siting

Current by-county distribution forces analysis to use single value or equal distribution





How can Spatial Statistics Help in Biomass?

- Allocate resource to specific areas within a county
- Quantify residue that could be collected within 50, 75, and 100 miles radius from a power plant
- Determine the type of residue that dominates within the radius



Uncertainty in Solar Radiation Estimates can Directly Influence Success of Concentrating Solar Projects

- Direct Normal Irradiance (DNI) modeled estimates have an uncertainty that ranges up to +/- 20%
- Break-even annual DNI for Concentrating Solar Power (CSP) plants is generally considered to be DNI = 7000 whr/m²/day
- DNI values are highly dependent on AOD (Aerosol Optical Depth), which is hard to measure.
- Clean air prospecting with better aerosol data will reduce uncertainty of DNI estimates.




Example Analysis Project: Southwest Aerosol Optical Depth


- AOD critical input for CSP solar modeling
- Previous study for 1996 solar maps:
- ✓ Used surface DNI measurements, plus other data inputs to "back out" AOD.
- Did not adjust for elevation
- Used a simplified seasonal pattern
- For new aerosol data, we wanted to:
- Use new high quality surface AOD measurements
- ✓ Use more realistic seasonal patterns over deserts
- ✓ Adjust AOD for elevation.




DNI Very Sensitive to Aerosol Optical Depth (AOD)




Southwestern Seasonal Aerosol Patterns




Annual AOD vs Elevation



Annual AOD Adjusted to Sea Level



Annual Average DNI - Change with Enhanced Aerosols



Possible Enhancements to Reduce AOD and Hence DNI Uncertainty?

- Evaluate uncertainty of AOD estimates using surface data locations, terrain complexity, other data, statistical methods?
- Evaluate reduction in uncertainty if we get new data from a hypothetical location.
- Process many proposed locations to choose optimum location for new surface measurements.



Potential Data Sets For Regionalization To Support National Level Models

Renewable Energy Resources

- Wind resources, long-term regional multipliers
- Wind Supply/Demand, Capacity factors by time of day/season
- Biomass supply
- Geothermal resources
- Solar insolation for distributed PV & CSP systems
- PV & CSP capacity factors by time of day/season
- Hydro resource or supply curves for new sites
- Hydroelectric Conventional Net Summer Capacity
- Landfill Gas Yield Ratios



Potential Data Sets For Regionalization To Support National Level Models (cont)

Electricity

- T&D interconnection costs
- Extra T&D costs for wind
- T&D costs avoided by DG
- Electricity Demand
- Retail Sales of Electricity
- Average Retail Price of Electricity
- Electric generation plants
- Electric transmission lines
- Electric transmission line rating and available capacity

- Emissions by power plant
- Natural gas pipeline location and capacity
- Coal reserves
- Current coal capacity
- Coal consumption
- Current natural gas capacity
- Natural gas reserves
- Natural gas consumption
- Hydro capacity (river and flow rates?)



Potential Data Sets For Regionalization To Support National Level Models (cont)

Residential and Commercial

- Heating Degree Days and Cooling Degree Days
- Appliance shares (number of homes with freezers, DW, CW, CAC, Room AC)
- Pipeline capacity for gasfired DG
- Renewable energy incentives
- EPA designated nonattainment areas
- Clean Cities

- Major commercial/industrial users of electricity; demand, supply
- Population
- Household characteristics
- Energy consumption by source and end use sector
- Residential electric demand
- Military electric demand, supply




BACKUP SLIDES

Procedure For Updated AOD

- Process surface AOD from 6 stations (high quality, limited spatial extent)
- Use average monthly profiles for interior location in the Southwest. Assign profiles to every model grid cell with the help of outside (cloud) data.
- Derive elevation dependence of AOD
- Adjust annual mean values to sea level
- Resample to 10 km grid
- Adjust final aerosol values using 10 km elevation data.



Aerosol Station Values, 1996 CSR Data Grid






Data Grid DNI Stations

Annual BAOD

- 0.032 0.05
- 0.05 0.06
- 0.06 0.07
- 0.07 0.08
- 0.08 0.09
- 0.09 0.1
- 0.1 0.12
- 0.12 0.14
- 0.14 0.16
- 0.16 0.18
- **0.18 0.3**



Adjusting Aerosol Profiles in Southwest Using Elevation

